

Vorsprung in
Gebäudetechnik durch
Machine Learning

Lynus Hybrid Inverter
29.9/30/35/40/50K
SG01HP3-EU-BM2/3/4 |
29.9-50kW
Three Phase | 2/3/4 MPPT
High Voltage Battery



Funktionen & Eigenschaften

- 100% unsymmetrischer Ausgang, jede Phase;
Max. Ausgang bis zu 50% Nennleistung
- DC-Kopplung und AC-Kopplung zur
Nachrüstung einer bestehenden Solaranlage
- Max. 10 Stück parallel für netzgebundenen und
netzunabhängigen Betrieb; unterstützt mehrere
Batterien parallel
- Max. Lade-/Entladestrom von 50A
- Hochspannungsbatterie, höherer Wirkungsgrad

Modell	Lynus 29,9 kW Hybrid Inverter	Lynus 30 kW Hybrid Inverter	Lynus 35 kW Hybrid Inverter	Lynus 40 kW Hybrid Inverter	Lynus 50 kW Hybrid Inverter
Batterie-Eingangsdaten					
Battery Type	Lithium-ion				
Battery Voltage Range (V)	160-800				
Max. Charging Current (A)	50+50				
Max. Discharging Current (A)	50+50				
Number of Battery Input	2				
Charging Strategy for Li-Ion Battery	Self-adaption to BMS				
PV String Eingangsdaten					
Max. DC Input Power (W)	38870	39000	45500	52000	65000
Max. DC Input Voltage (V)	1000				
Start-up Voltage (V)	180				
MPPT Range (V)	150-850				
Full Load DC Voltage Range (V)	360-850	360-850	360-850	360-850	450-850
Rated DC Input Voltage (V)	600				
PV Input Current (A)	36+36+36	36+36+36	36+36+36	36+36+36+36	
Max. PV I _{SC} (A)	55+55+55	55+55+55	55+55+55	55+55+55+55	
No.of MPP Trackers	3			4	
No.of Strings per MPP Tracker	2+2+2			2+2+2+2	
AC-Ausgangsdaten					
Rated AC Output Active Power (W)	29900	30000	35000	40000	50000
Max AC Output Active Power (W)	29900	33000	38500	44000	55000
AC Output Rated Current (A)	45.4/43.4	45.5/43.5	53.1/50.8	60.7/58	75.8/72.5
Max. AC Output Rated Current (A)	45.4/43.4	50/47.8	58.4/55.8	66.7/63.8	83.4/79.7
Max. Three-phase Unbalanced Output Current (A)	60	60	60	70	83.3
Max. Continuous AC Passthrough (A)	200				
Peak Power (Off Grid)	1.5 time of rated power, 10 S				
Generator Input/Smart Load /AC Couple Current (A)	45.4 / 200 / 45.4	45.5 / 200 / 45.5	53.1 / 200 / 53.1	60.7 / 200 / 60.7	75.8 / 200 / 75.8
Power Factor Adjustment Range	0.8 leading to 0.8 lagging				
Output Frequency and Voltage	50/60Hz; 3L/N/PE 220/380, 230/400Vac				
Grid Type	Three Phase				
Total Harmonic Distortion (THD)	<3% (of nominal power)				
DC Current Injection	<0.5% I _N				
Wirkungsgrad					
Max. Efficiency	97.60%				
Euro Efficiency	97.00%				
MPPT Efficiency	99.90%				
Schutz					
Integrated	Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge Protection				
Over Voltage Category	DC Type II/AC Type III				
Zertifizierungen und Normen					
Grid Regulation	VDE4105, IEC61727/62116, VDE0126, AS4777.2, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002, NBR16149/NBR16150				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
Allgemeine Daten					
Operating Temperature Range (°C)	-40-60°C, >45°C derating				
Cooling	Smart cooling				
Noise (dB)	≤65 dB				
Communication with BMS	RS485; CAN				
Weight (kg)	80				
Size (mm)	527W×894H×294D				
Protection Degree	IP65				
Installation Style	Wall-mounted				
Warranty	5 Years (10 Years Optional)				

*Note: The function of Multiple units work in parallel mode will be available in Q1 2023